



# ACCURACY INTERNATIONAL AXMC

AXMC rifles are available in 338, .300 or .308 calibre. Armed with an AXMC calibre conversion kit, a user can easily change the original calibre in minutes.

## CALIBRES

.338 Lap Mag | .300 Win Mag | .308 Win

## WEIGHT

6.8kg (15lb)  
with standard rail setup, empty magazine,  
no scope, 27" barrel, tactical muzzle brake

## DIMENSIONS

Full length: 1250mm x 185mm x 100mm  
Stock folded: 1040mm x 185mm x 105mm  
with 27" barrel, tactical muzzle brake

## FEATURES

Proofed steel action featuring AI's patent pending Quickloc quick release barrel system, bolted and bonded to aluminium chassis

30 MOA STANAG 4694 / Mil Std 1913 action and forend rail

6 lug, 60° bolt with AI combat proven leaf spring extractor

3 position safety

Two stage trigger adjustable for reach and trigger weight between 1.5 and 2kg

Detachable 10-round CIP length double stack magazine - can also be top loaded though the rifle ejection port

Left side magazine port cut out for ease of magazine insertion

## BASE MODELS

Right side folding stock over bolt

Adjustable cheekpiece

Adjustable buttpad with spacers

Pistol grip

Flush cup sling attachment points

30 MOA STANAG 4694 / Mil Std 1913 action rail and 16" forend tube and rail

Double chamber standard muzzle brake

1 x 140mm plain accessory rail

2 x 80mm flush cup accessory rails

User manual

1 x 10 round double stack CIP magazine

## COLOURS

AX rifles benefit from a Cerakote ceramic polymer firearm coating. Choose from:

High performance in three unique AI colours



Elite ultra high performance for unrivalled durability



## AI BARREL OPTIONS

.338 LM: 20" / 27" 1 in 9.35" twist, stainless steel, plain threaded for muzzle brake

.300 Win Mag: 20" / 24" / 26" 1 in 11" twist, stainless steel, plain threaded for muzzle brake

.308 Win: 20" / 24" / 26" 1 in 12" twist, stainless steel, plain threaded for muzzle brake

## OPTIONS

Tactical threaded double chamber muzzle brake for AI suppressor

## ACCESSORIES

STANAG 4694 / Mil std 1913 accessory rails to attach to AI's patented KeySlot™ mounting system

AI Bipod and mounts for other bipod brands (including Harris)

Rear butt spikes

Calibre conversion kits (also see reverse): .338 LM, .300 WM and .308 Win\* comprising barrel, bolt & magazine \*includes long action magazine converter

Handstop with sling loop and flush cup

Suppressor

Slings | Transit cases | Cleaning kits

# AI AXMC MULTI CAL SYSTEM COMPONENTS



## TORQUE WRENCH

(preset 5.5Nm with 4mm bit)



## AI AXMC RIFLE FITTED WITH .338 LAP MAG KIT

Bolt (identified by ●●●)

Barrel (identified by ●●●) shown here with tactical muzzle brake option  
Magazine

Changing calibre is as simple as ABC  
and takes just a few minutes...

### A CHANGE BARREL

Loosen the barrel clamp screw with the pre-set torque wrench supplied and unscrew the barrel.

Hand tighten the selected calibre barrel and tighten the barrel clamp screw with the pre-set torque wrench.



## .300 WIN MAG KIT

Bolt (identified by ●●)

Barrel (identified by ●●) shown here with tactical muzzle brake option  
Magazine

### B CHANGE BOLT

Slide the bolt from the rifle, take out the shroud / firing pin and insert it in the chosen calibre bolt. Slide the chosen bolt assembly into the rifle.



## .308 WIN / 7.62MM KIT

Bolt (identified by ○)

Barrel (identified by ○) shown here with tactical muzzle brake option  
Magazine converter  
Magazine

### C CHANGE MAGAZINE

Note: For 308/7.62mm calibre, insert the .308/7.62mm magazine converter into the magazine aperture before loading the magazine.

Accuracy International Ltd

Portsmouth, UK

T: + 44 (0) 23 92 67 1225

E: ai@accuracyinternational.org

W: www.accuracyinternational.com

©Accuracy International 2017. All rights reserved, specification may be subject to change without notice

