



ACCURACY INTERNATIONAL AXMC

CALIBRE

.338 Lapua
.300 Win mag

WEIGHT

6.6Kg (14.6lb)
*Empty magazine, no scope,
27" barrel with muzzle brake*

DIMENSIONS

Full length
1225mm x 180mm x 90mm
Stock folded
965mm x 180mm x 100mm)
27" barrel, no scope

FEATURES

Proofed steel action featuring AI's patent pending Quickloc quick release barrel system, bolted and bonded to aluminium chassis

30 MOA STANAG 4694 / Mil Std 1913 action and forend rail

6 lug, 60 degree bolt with AI combat proven leaf spring extractor

3 position safety

Two stage trigger adjustable for trigger weight between 1.5 and 2Kg

Detachable 10-round CIP length double stack magazine - can also be top loaded through the rifle ejection port

Left side magazine port cut out for ease of magazine insertion

BASE MODELS

Right side folding stock over bolt

Adjustable cheekpiece

Adjustable butt pad with spacers

Pistol grip

Flush cup sling attachment points

30 MOA STANAG 4694 / Mil Std 1913 action rail and 16" forend tube and rail

Double chamber standard muzzle brake

1 x 140mm plain accessory rail

2 x 80mm flush cup accessory rails

User manual

1 x 10 round double stack CIP magazine

Colours: black or green stocksides with black metalwork or pale brown stocksides and metalwork

FACTORY BARREL OPTIONS

.338 LM: 20" / 27" 1 in 9.35" twist, stainless steel, plain threaded for muzzle brake

.300 Win Mag: 20" / 24" / 26"
1 in 11" twist, stainless steel, plain threaded for muzzle brake

.308 Win: 20" / 24" / 26" 1 in 12" twist, stainless steel, plain threaded for muzzle brake

OPTIONS

Tactical threaded double chamber muzzle brake for AI suppressor

ACCESSORIES

STANAG 4694 / Mil std 1913 accessory rails to attach to AI's patented KeySlot™ mounting system

Bipods

Rear butt spikes

Calibre conversion kits:
.338 LM barrel, bolt & magazine
.300 WM barrel, bolt & magazine
.308 Win (long action) barrel, bolt, magazine and mag converter

AI bipod and Harris bipod mount

Handstop with sling loop and Flush cup

Suppressor

Slings

Transit cases

Cleaning kits

©Accuracy International 2014. All rights reserved, specification may be subject to change without notice